

TTA trail extension spring tandem holders

Trail Extension Spring Tandem Holders 7¹/₂°

Construction

- Brass Die Casting with dividing wall between boxes
- Pressure finger sheet brass
- Stainless steel finger blade with insulated tip
- Bronze pivots
- Stainless steel pivot pins
- Natural Finish
- Brush box to I.E.C E.10 tolerances
- Alternative Mounting faces available on request



Part No.	Holder Type	Nominal Dimensions (mm)				Imperial/Metric	'U' Throw (Fixing) Dimensions (mm)	Spring Load (gf)	Serrated (Y/N)	No. Pockets	Fabricated/ Cast
		t	a	Box Height	Brush Length						
TTA2006M/50	TTA	10+10	32.00	50.00	50.00	Metric	15.00	230	Y	2	Cast
TTA2008M/53	TTA	2.5+12.5	32.00	50.00	50.00	Metric	15.00	200	N	2	Cast
TTA2008M/50	TTA	2.5+12.5	32.00	50.00	50.00	Metric	15.00	200	Y	2	Cast
TTA2008M/57	TTA	2.5+12.5	32.00	50.00	50.00	Metric	14.50	250	N	2	Cast
TTA2008M/58	TTA	2.5+12.5	32.00	50.00	50.00	Metric	8.00	200	register	2	Cast
TTA2010M/50	TTA	16.0+16.0	32.00		50.00	Metric	15.00	200	Y	2	Cast
TTA2010M/54	TTA	16.0+16.0	32.00	58.00	50.00	Metric	15.00	200	Y	2	Cast

PTO

Công ty TNHH Trí Lập
Phòng 602+604, tòa nhà Vinahud
đường Trung Yên 9, KĐT Trung Yên
P. Trung Hòa, Q. Cầu Giấy, Hà Nội

TriLAP Company Limited
Suite 602+604, Vinahud Building
Trung Yen 9 Road, Trung Hoa Ward
Cau Giay Dist., Ha Noi, Viet Nam

Tel: (84-24) 6682 0666
Fax: (84-24)3226 2435
Hotline: 090 414 6666/ 098 873 8818
www.trilap.com.vn/

TTA trail extension spring tandem holders

